




TOP




SIDE VIEW



END VIEW



MODEL



PLATING - SURFACE TREATMENT

LAYER	METRIC	BSC
Ni	3.0 ~ 6.0 μm	120 ~ 240 $\mu\text{-inch}$
Au Flash	0.05 ~ 0.20 μm	2 ~ 8 $\mu\text{-inch}$

Physical Properties

Coefficient of thermal expansion $\times 10^{-5}/^{\circ}\text{C}$	Thermal conductivity $\text{W}/(\text{m}^{\circ}\text{K})$	Electrical conductivity $\% \text{IACS}$	Modulus of elasticity GPa	Density g/cm^3
17.3	340	85	118	8.9

NOTES:

1. DIMENSIONS MM (UNLESS OTHERWISE SPECIFIED).
2. BASE METAL EFTEC-3 (UNS C14410) COPPER ALLOY.
3. ALLOY MASS% Cu99.9/Sn0.1
4. TEMPER: ANNEALED. VICKERS HARDNESS (HV) ~65

APPROVALS	DATE				
DRAWN T. Au	2/01/2025				
ENG M. Hart	2/01/2025	TITLE CU110G8x63A COPPER ALLOY STRAIGHT PIN			
MFG					
QA		SCALE 30:1	SIZE A	DRAWING NO. 600863	REV A
CUST					
REVISED		DO NOT SCALE DRAWING			SHEET 1 OF 2

PART NUMBERING SYSTEM

CU110	G	8	X	63	A
COPPER ALLOY	PLATING	DIAMETER	PACKING	LENGTH	TEMPER
Cu99.9 / Sn0.10 EFTEC-3 UNS C14410	G = ENIG FLASH GOLD Ni 3.0um (120u-inch) Au 0.20um (8 u-inch)	8 MIL = 0.20mm	BULK	63 MIL = 1.6mm	A = ANNEALED

DRAWING NUMBER

60	08	63																																		
ALLOY	DIAMETER	LENGTH																																		
60 = Cu99.9 / Sn0.10 ANNEALED	<table><tr><th>MIL</th><th>MM</th></tr><tr><td>06</td><td>0.15</td></tr><tr><td>08</td><td>0.20</td></tr><tr><td>10</td><td>0.25</td></tr><tr><td>12</td><td>0.30</td></tr><tr><td>14</td><td>0.35</td></tr><tr><td>15</td><td>0.38</td></tr><tr><td>16</td><td>0.40</td></tr></table>	MIL	MM	06	0.15	08	0.20	10	0.25	12	0.30	14	0.35	15	0.38	16	0.40	<table><tr><th>MIL</th><th>MM</th></tr><tr><td>25</td><td>0.63</td></tr><tr><td>31</td><td>0.80</td></tr><tr><td>40</td><td>1.00</td></tr><tr><td>50</td><td>1.27</td></tr><tr><td>60</td><td>1.52</td></tr><tr><td>63</td><td>1.60</td></tr><tr><td>75</td><td>1.90</td></tr><tr><td>87</td><td>2.21</td></tr></table>	MIL	MM	25	0.63	31	0.80	40	1.00	50	1.27	60	1.52	63	1.60	75	1.90	87	2.21
MIL	MM																																			
06	0.15																																			
08	0.20																																			
10	0.25																																			
12	0.30																																			
14	0.35																																			
15	0.38																																			
16	0.40																																			
MIL	MM																																			
25	0.63																																			
31	0.80																																			
40	1.00																																			
50	1.27																																			
60	1.52																																			
63	1.60																																			
75	1.90																																			
87	2.21																																			

TopLine®			
TITLE CU110G8x63A COPPER ALLOY STRAIGHT PIN			
SCALE 30:1	SIZE A	DRAWING NO. 600863	REV A
DO NOT SCALE DRAWING			SHEET 2 OF 2